

RETI ELETTRICALDATE

Dati generali

Finitura: grezza, zincata e Inox

Rete elettrosaldata standard in pannelli da mm 1000x2000, 1200x2400 e su richiesta (solo per alcuni formati) fino a 1600x5000.

Diametro del filo: da 3 a 6 mm.


Maglie: da 25x25 mm fino a 100x100 mm

Dimensioni Maglia		Spessore Filo	Dimensioni Pannello		
H	L	Ø	H	L	Peso
mm	mm	mm	mm	mm	kg/m2
25	25	3	1000	2000	5,6
30	30	3	1000	2000	3,43
30	30	3	1200	2400	3,43
40	40	3	1000	2000	2,6
40	40	3	1200	2400	2,6
40	40	4	1000	2000	4,7
40	40	4	1200	2400	4,7
50	50	3	1000	2000	2,08
50	50	3	1200	2400	2,08
50	50	4	1000	2000	3,76
50	50	4	1200	2400	3,76


ANTINFORTUNISTICA

Dimensioni Maglia		Spessore Filo	Dimensioni Pannello		
H	L	Ø	H	L	Peso
mm	mm	mm	mm	mm	kg/m2
TEC 15/105/15	15	3	1000	2000	4,27
TEC 15/105/15	15	3	1240	2400	4,27
RT 60	11	3	1200	2400	5,46

Maglia QUADRA



Maglia RT



Maglia TEC

